MONITEX®

MONITEX® 4 Gas Monitor

4 Gas Monitor

The 4 Gas Monitor combines quality, ruggedness and advanced technology in a user friendly, portable gas monitor. It is compact, lightweight, water resistant, extremely robust, and it is certified to multiple international and regional standards.

It can measure any combination of LEL, O2, CO and H2S making it suitable for a wide range of personal monitoring and confined space applications. In addition to extensive datalogging capabilities, the 4 Gas Monitor is available with an internal pump and an extensive range of accessories to meet a wide variety of user applications.

Features & Benefits

- Simple 2-button operation
- Any combination of LEL/O2/CO/H2S
- Audible, visual and vibrating alarms
- Fully certified
- Datalogging capabilities (up to 6 months)
- Run-time up to 80 hours, when using low power LEL sensor (optional)
- Lightweight
- Robust construction

Key Applications

- Confined spaces
- Basements
- Tunnels
- Shafts
- Personal Monitoring

Technical Specifications	
Size	121 x 59 x 32mm
Weight	230g
Temperature	-20°C to +50°C
Humidity	0 to 95% R.H non-condensing
Alarms:	Highly visible flashing LED, piercing >90dB audible, vibrating
Display	Green and red LCD backlight display
Battery	Lithium Ion rechargeable battery
Charging Time	< 4 hrs
Enclosure	High impact rubberized polycarbonate case
Approvals	ATEX II Ex 2G Ex ia d IIC T4 Gb IECEx Ex ia d IIC T4 Gb ATEX Ex II 1G Ex ia IIC T4 Ga* IECEx Ex ia IIC T4 Ga*

Request Price

Prospect House
Unit 5
Click Industrial Estate
Aylesford
Kent
ME20 7NY

T.+44 (0) 844 324 0601
F.+44 (0) 844 324 0602
E. info@rvtgroup.co.uk

www.rvtgroup.co.uk

©Copyright RVT Group Ltd 2026

RVTGROUP™
Protecting people and our environment