



4 Gas Monitor

The 4 Gas Monitor combines quality, ruggedness and advanced technology in a user friendly, portable gas monitor. It is compact, lightweight, water resistant, extremely robust, and it is certified to multiple international and regional standards.

It can measure any combination of LEL, O2, CO and H2S making it suitable for a wide range of personal monitoring and confined space applications. In addition to extensive datalogging capabilities, the 4 Gas Monitor is available with an internal pump and an extensive range of accessories to meet a wide variety of user applications.

| Features & Benefits |
|---|
| ✔ Simple 2-button operation |
| ✔ Any combination of LEL/O2/CO/H2S |
| ✔ Audible, visual and vibrating alarms |
| ✔ Fully certified |
| ✔ Datalogging capabilities (up to 6 months) |
| ✔ Run-time up to 80 hours, when using low power LEL sensor (optional) |
| ✔ Lightweight |
| ✔ Robust construction |

| Key Applications |
|-----------------------|
| ✔ Confined spaces |
| ✔ Basements |
| ✔ Tunnels |
| ✔ Shafts |
| ✔ Personal Monitoring |

| Technical Specifications | |
|--------------------------|--|
| Size | 121 x 59 x 32mm |
| Weight | 230g |
| Temperature | -20°C to +50°C |
| Humidity | 0 to 95% R.H non-condensing |
| Alarms: | Highly visible flashing LED, piercing >90dB audible, vibrating |
| Display | Green and red LCD backlight display |
| Battery | Lithium Ion rechargeable battery |
| Charging Time | < 4 hrs |
| Enclosure | High impact rubberized polycarbonate case |
| Approvals | ATEX II 2G Ex ia d IIC T4 Gb IECEX Ex ia d IIC T4 Gb ATEX II 1G Ex ia IIC T4 Ga* IECEX Ex ia IIC T4 Ga* |



[Request Price](#)