



# Water Treatment

## EnviroHub® TU02 Dosing Skid

### EnviroHub® TU02 Dosing Skid

The TU02 dosing skid is used with treatment tanks to automatically add flocculant and coagulant as required to make fine suspended solids easier to remove while discharging water. Used with Lamella settlement tanks to settle the solids as a sludge.

#### Features

- ✓ 2no IBC of reagent storage capacity
- ✓ Sufficiently bunded to prevent spillages
- ✓ On-board enclosure for dosing pumps (peristaltic)
- ✓ On-board control to ensure correct proportionate dosing
- ✓ Automated alert when IBCs is near empty
- ✓ Fork pockets and lifting points

#### Technical Data

Mass (Empty)	450kg
Mass (Full)	17,000kg
Length	2.63m
Width	1.35m
Height	2.09m
Area/Capacity	1.2m <sup>3</sup> Bund Capacity
Required Minimum Fork Length	0.66m



[Request Price](#)



# Water Treatment

## EnviroHub® TU02 Dosing Skid



Prospect House  
Riverside Way  
Dartford  
Kent  
DA1 5BS

T.+44 (0) 844 324 0601  
F.+44 (0) 844 324 0602  
E. [info@rvtgroup.co.uk](mailto:info@rvtgroup.co.uk)  
[www.rvtgroup.co.uk](http://www.rvtgroup.co.uk)

©Copyright RVT Group Ltd 2020



**RVTGROUP**<sup>TM</sup>  
Protecting people and our environment