



# CLIMEX®

## CLIMEX® Indirect Oil-Fired Heater 170S

### CLIMEX® Indirect Oil-Fired Heater 170S

This 170kW static oil-fired heater, economically provides large volumes of fume-free dry heat.

Heat is created by convection: flames heat up the heat exchanger so that the surrounding air is heated as it passes over the chamber, creating hot dry 100% fume-free clean air. The 600mm duct outlets enable warm air to be distributed to enclosed areas up to 180 metres away.

The static oil fired heater has been robustly constructed: the heater housing remains cool to the touch, and is rated to IP44 for weather protection. The heater can be fitted with a wireless thermostat, with a range of 200 metres.

They are designed to be used with a three-phase electric supply of 415 volts, 3 phases, 50Hz, 32amp. The static oil fired heater utilises the latest Rectus environmental oil couplings, which are fitted with a valve. The valves close automatically when disconnected, which prevents any oil from leaking.

#### Features & Benefits

- ✓ Thermostat options with a 200mtr range
- ✓ Optional re-circulation ducts for maximum efficiency
- ✓ Capable of long duct runs
- ✓ Quiet in operation

#### Key Applications

- ✓ Drying out of new build construction projects
- ✓ Heating or maintaining ambient temperatures



[Request Price](#)



# CLIMEX®

## CLIMEX® Indirect Oil-Fired Heater 170S

### Technical Specifications

Nominal Heating Capacity Full Load	170kw
Airflow m3/hr	13140
Noise Level @ 3m	63 dBa
Outlet Duct	4 x 300mm
Electrics	415v 32a 5 pin
Fuel Consumption on full load	17 Litres/hr
Heater Dimensions cm	L 270 W 83 H 180
Weight Kg	725



Prospect House  
Riverside Way  
Dartford  
Kent  
DA1 5BS

T.+44 (0) 844 324 0601  
F.+44 (0) 844 324 0602  
E. info@rvtgroup.co.uk

[www.rvtgroup.co.uk](http://www.rvtgroup.co.uk)

©Copyright RVT Group Ltd 2020



**RVTGROUP**<sup>™</sup>  
Protecting people and our environment