



CLIMEX®

CLIMEX® Indirect Oil-Fired Heater 65kW

CLIMEX® Indirect Oil-Fired Heater 65kW

A highly efficient unit, ideal for drying out new build construction projects.

Manoeuvrable and compact, this 65kW heater is excellent for sites with limited space. It can even be wheeled through buildings (along with a mobile fuel buggy) to reach difficult locations. The 65M is commonly used for drying out a specific area or individual floor within a building; such as a school, retirement home or commercial block.

Remote thermostats can be used to ensure maximum fuel efficiency.

Incorporating a sealed combustion chamber and heat exchanger, the 65M supplies only warm, dry, fume-free air inside buildings. All combustible fumes are vented from the heater outside. By displacing cold, damp air with warm and dry air, the 65M will dry areas far more effectively, efficiently and safely than traditional electric heaters, red-rads or space heaters.

The heater runs on red diesel which must be supplied from a dedicated bunded fuel tank. It also requires a 110v 32a supply to power the electric fan.

Features & Benefits	Key Applications
<ul style="list-style-type: none">✓ 65kW of heat from a single 110v 32a supply✓ Excellent fuel economy - 91% efficient✓ A mobile unit that can easily be moved around site as work progresses✓ A ductable unit that ensures even warm air distribution	<ul style="list-style-type: none">✓ Drying out of new build construction projects✓ Heating or maintaining ambient temperatures

Upgrade to our New Wireless Remote Thermostat!



[Request Price](#)



CLIMEX®

CLIMEX® Indirect Oil-Fired Heater 65kW

Technical Specification

Heat Output	65kW
Heat Output (BTU)	221,780
Airflow	4,000m ³ /h
Maximum Fuel Consumption	6.5L per hour
Heater Fuel Line	3/8" male connector
Ducting Diameter	450mm
Plug	32a 3-pin
Voltage	110v
Running Current	15 amps
Remote Thermostat	Optional Extra
Max. recommended extension lead run	20m
Minimum Power Supply	'D' rated circuit breaker (10Kva continuous transformer recommended)
Length	1,990mm
Width	710mm
Height	1,280mm
Weight	245kg
Noise Level*	75.5Dba

*Noise levels are given as a guidance only, as the location and loading of the heater will affect the final noise output.

Upgrade to our New Wireless Remote Thermostat

This unit features an integrated thermostat as standard, however you may prefer to upgrade to a wireless remote thermostat for a small additional cost. Please ask us for pricing when you book your heater!

Technical Details for the New Wireless Remote Thermostat:

Dimensions	206mm l x 167mm w x 90mm d
Range from heater	50-100 metres
Battery Operated	Yes x 2 AA
Weight	Up to 1kg
Cloud Based?	No
No software required	



The Effective Drying Triangle

For drying out programmes to work effectively, a combination of heat, air movement and dehumidification is required; all of which can be achieved by using an indirect oil-fired heater.



Warmth- Heat raises the room temperature and so lowers the relative humidity of the air. This allows the air to absorb more water from surrounding surfaces.

Air Movement- Air movement across a substrate draws the water to the surface, where it evaporates.

Dehumidification- Dehumidification extracts water from the air.



CLIMEX®

Images on site



Prospect House
Riverside Way
Dartford
Kent
DA1 5BS

T.+44 (0) 844 324 0601
F.+44 (0) 844 324 0602
E. info@rvtgroup.co.uk

www.rvtgroup.co.uk

©Copyright RVT Group Ltd 2020



RVTGROUP™
Protecting people and our environment