



CLIMEX®

CLIMEX® Air Handler Unit 250-500

CLIMEX® Air Handler Unit 250-500

This CLIMEX® Air Handler Unit can be used to provide air conditioning, heating or ventilation.

The Air Handling unit can be connected to a water chiller to provide large scale air conditioning, connected to a heating boiler to provide high volumes of warm air or used stand alone to provide ventilation.

This 250kW/500kW unit has variable speed options and is environmentally friendly.



Features & Benefits
✓ Environmentally Friendly
✓ Variable Speed options
✓ Condensate pump option
✓ Easy Installation, plug and play
✓ Easy, quick release water connections
✓ Simple electrical Connections
✓ Easy to use control system

Key Applications
✓ Marquees
✓ Factories
✓ Exam halls
✓ Server rooms
✓ Data centres
✓ Large scale air conditioning
✓ Events and Exhibitions
✓ Process cooling
✓ Cold storage facilities
✓ Food processing
✓ Supermarkets

Technical specifications	
Nominal cooling capacity	250-500kW @ 80oC / 70oC return
Nominal heating capacity	500 kw
Airflow	30060M3/hr @ 400Pa
Return/ Inlet Air	4 off 640mm Diameter
OutletDuct	4 off 640mm Diameter
Electrics	415V 3PN & E Full load current 22.6 amps Start-up current 132 amps
Plug	BS4343 5 pin 32amp
Length / Width / Height	3600 / 2300 / 2200

[Request Price](#)

